

# SDR-6200 IrDA

## UHF 2-way Synchronizing True Diversity Receiver

### General Features

- EIA Standard 1/2U rack-mountable metal chassis with high contrast LCD display. (Channel, frequency, RF level, AF level and antenna selection)
- 100 factory preset user-selectable UHF channels.
- True diversity reception for best performance and reliability.(SDR-6200 IrDA)
- Adjustable SQ. Increases receiver range with higher sensitivity and reduces interference with lower sensitivity.
- Auto Scan function allows quick search for an interference-free working channel from 100 presets. World-first patented IrDA technology provides rapid and precise 2-way frequency sync between the receiver and transmitter.
- Receiver provides power for CHIAYO antenna systems to enhance reception range and signal stability.
- Audio output jacks: balanced XLR or unbalanced 6.3mm

### Specifications

Model	SDR-6200 IrDA
Channel	Single
Chassis	EIA standard 19" 1/2U
Frequency Range	UHF 500 – 960 MHz
Bandwidth	25 MHz
Receiving Mode	True diversity
Peak Deviation	± 40 kHz
Channel Sync	2-way (RX-to-TX)
Sensitivity	S/N > 80 dBm at 10 dBμV
S/N Ratio	> 110 dB (A)
T.H.D.	< 0.5% @ 1 kHz
Frequency Response	50 Hz – 18 kHz
Receiving Antenna	Rear Panel. Detachable.
Preset Channels	100
Oscillation Mode	PLL synthesized, frequency stability $\leq \pm 0.005\%$ (-10 – +60°C)
Squelch	Pilotone & Noise-cancelling dual-squelch circuit
Audio Output Adjustment	Gain control circuit for adjustment of output volume
Output Connector	Balanced XLR and unbalanced 6.3 Ø
Power Supply	12V DC · 1.0A
Power Consumption	12 W
Dimensions (W x H x D)	200 x 44 x 150 mm
Weight	0.63kg



\*\* Specifications and design are subject to change without prior notice.

Wireless Microphone System